

#### COREL ITALY LD5130



# **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

#### Supplier's name or trade mark: COREL ITALY

Supplier's address: Amministrazione, Triumplina 28, 25123 Brescia Brescia BS, IT

### Model identifier: LD5130

## Type of light source:

| Lighting technology used:     | LED  | Non-directional or directional: | NDLS |  |  |  |
|-------------------------------|------|---------------------------------|------|--|--|--|
| Light source cap-type         | E14  |                                 |      |  |  |  |
| (or other electric interface) |      |                                 |      |  |  |  |
| Mains or non-mains:           | NMLS | Connected light source (CLS):   | No   |  |  |  |
| Colour-tuneable light source: | No   | Envelope:                       | -    |  |  |  |
| High luminance light source:  | No   |                                 |      |  |  |  |
| Anti-glare shield:            | No   | Dimmable:                       | No   |  |  |  |
| Product parameters            |      |                                 |      |  |  |  |

|   |                                 | Product para            | lielers   |              |  |  |
|---|---------------------------------|-------------------------|---|--------------|--|--|
| Parameter   |                                 | Value                   | Parameter   | Value        |  |  |
| General product parameters:   |                                 |                         |   |              |  |  |
| Energy consumpt<br>mode (kWh/1000<br>up to the nearest in                                     | h), rounded                     | 5                       | Energy efficiency<br>class  | G            |  |  |
| Useful luminous<br>indicating if it refe<br>in a sphere (360º<br>cone (120º) or in a<br>(90º) | rs to the flux<br>?), in a wide | 400 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 6 500        |  |  |
| On-mode pow<br>expressed in W   | ver (P <sub>on</sub> ),         | 5,0                     | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00         |  |  |
| Networked standby<br>for CLS, expressed<br>rounded to the sec                                 | d in W and                      | -                       | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 80           |  |  |
| Outer H   | eight                           | 80                      | Spectral power  | See image    |  |  |
|   | /idth                           | 45                      | distribution in the   | in last page |  |  |
| without D   | epth                            | 45                      | -   |              |  |  |
| I   | -                               | 1                       | 1   | Pagina 1 /   |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) |      | range 250 nm to 800<br>nm, at full-load |       |  |  |  |
|--|------|---|-------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>   | -    | If yes, equivalent power (W)            | -     |  |  |  |
|  |      | Chromaticity                            | 0,313 |  |  |  |
|  |      | coordinates (x and y)                   | 0,337 |  |  |  |
| Parameters for LED and OLED light sources:   |      |   |       |  |  |  |
| R9 colour rendering index value  | 5    | Survival factor                         | 0,90  |  |  |  |
| the lumen maintenance factor   | 0,94 |   |       |  |  |  |
| (a)  |      | 1                                       |       |  |  |  |

(a)'-' : not applicable;

(b)'-' : not applicable;

