COREL ITALY

Ld5165

В

D E

F G

G O





9 kWh/1000h

Product Information Sheet

without

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	PELEGATED REGUI	LATION (EU) 2019/2	o15 with regard to energ	gy labelling of light	
Supplier's name	e or trade mark:	COREL ITALY			
Supplier's addre	ess: Amministraz	ione, Triumplina 28	, 25123 Brescia Brescia I	BS, IT	
Model identifie	r: Ld5165				
Type of light so	urce:				
Lighting technology used:		other HID	Non-directional or directional:	NDLS	
Light source cap-type		E27			
(or other electri	ic interface)				
Mains or non-mains:		NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:		No	Envelope:	-	
High luminance light source:		No			
Anti-glare shield:		No	Dimmable:	No	
Product parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		9	Energy efficiency class	F	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		820 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode power (P _{on}), expressed in W		9,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer dimensions	Height Width	108 60	Spectral power distribution in the	See image in last page	
11	vviutii	טס		idst page	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	- If yes, equivalent power (W)	-
	Chromaticity coordinates (x and y)	0,380 0,380

(a)'-': not applicable; (b)'-': not applicable;

