## **ENERG**<sup>5</sup> **COREL ITALY**

LD5610

В

G 15

kWh/1000h

## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources  | LLLOAILD KLOOI   | -A11014 (L0) 2013/2       | 015 with regard to energ   | gy labelling of light |
|--|------------------|---------------------------|--|-----------------------|
| Supplier's name  | e or trade mark: | COREL ITALY               |  |                       |
| Supplier's addr  | ess: Amministraz | ione, Triumplina 28       | , 25123 Brescia Brescia I  | BS, IT                |
| Model identifie  | er: LD5610       |                           |  |                       |
| Type of light so   | urce:            |                           |  |                       |
| Lighting techno  | logy used:       | LED                       | Non-directional or directional:  | NDLS                  |
| Light source cap<br>(or other electr   | • •              | E27                       |  |                       |
| Mains or non-m   | nains:           | NMLS                      | Connected light source (CLS):  | No                    |
| Colour-tuneable  | e light source:  | No                        | Envelope:  | -                     |
| High luminance   | light source:    | No                        |  |                       |
| Anti-glare shield  | d:               | No                        | Dimmable:  | No                    |
|  |                  | Product para              |  |                       |
| Parameter  |                  | Value                     | Parameter  | Value                 |
|  |                  | General product p         |  | T                     |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |                  | 15                        | Energy efficiency class  | F                     |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |                  | 1 521 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000                 |
| On-mode power (P <sub>on</sub> ), expressed in W   |                  | 15,0                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,00                  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |                  | -                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80                    |
| Outer  | Height           | 123                       | Spectral power   | See image             |
| dimensions   | Width            | 60                        | distribution in the  | in last page          |
| without  | Depth            | 60                        |  | Pagina 1 /            |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) |      | range 250 nm to 800<br>nm, at full-load |       |  |  |  |
|--|------|---|-------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>   | -    | If yes, equivalent power (W)            | -     |  |  |  |
|  |      | Chromaticity                            | 0,380 |  |  |  |
|  |      | coordinates (x and y)                   | 0,380 |  |  |  |
| Parameters for LED and OLED light sources:   |      |   |       |  |  |  |
| R9 colour rendering index value  | 5    | Survival factor                         | 0,90  |  |  |  |
| the lumen maintenance factor   | 0,94 |   |       |  |  |  |

(a)'-': not applicable; (b)'-': not applicable;

