

#### COREL ITALY LD8158







# **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

#### Supplier's name or trade mark: COREL ITALY

Supplier's address: Amministrazione, Triumplina 28, 25123 Brescia Brescia BS, IT

### Model identifier: LD8158

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	E27				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

		Product para	lieleis			
Parameter		Value	Parameter	Value		
General product parameters:						
• ·	mption in on- 000 h), rounded est integer	8	Energy efficiency class	E		
indicating if it in a sphere (3	pus flux (φuse), refers to the flux 360º), in a wide in a narrow cone	1 055 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode expressed in W	power (P <sub>on</sub> ), /	8,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
for CLS, expre	ndby power (P <sub>net</sub> ) essed in W and e second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer dimensions without	Height	175	Spectral power	See image		
	Width	125	distribution in the	in last page		
	Depth	125	1	Pagina 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity	0,440
		coordinates (x and y)	0,403
Parameters for LED and OLED ligh	nt sources:	· · ·	
R9 colour rendering index value	9	Survival factor	0,90
the lumen maintenance factor	0,94		
(a)		1	

(a)'-' : not applicable;

(b)'-' : not applicable;

