

## COREL ITALY







# **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

#### Supplier's name or trade mark: COREL ITALY

Supplier's address: -

#### Model identifier: LD8408

### Type of light source:

| Lighting technology used:     | LED  | Non-directional or directional: | NDLS |  |  |
|-------------------------------|------|---------------------------------|------|--|--|
| Light source cap-type         | E27  |                                 |      |  |  |
| (or other electric interface) |      |                                 |      |  |  |
| Mains or non-mains:           | NMLS | Connected light source (CLS):   | No   |  |  |
| Colour-tuneable light source: | No   | Envelope:                       | -    |  |  |
| High luminance light source:  | No   |                                 |      |  |  |
| Anti-glare shield:            | No   | Dimmable:                       | No   |  |  |
| Product parameters            |      |                                 |      |  |  |

| Parameter  |                                  | Value                     | Parameter   | Value        |  |  |
|--|----------------------------------|---------------------------|---|--------------|--|--|
| General product parameters:  |                                  |                           |   |              |  |  |
| Energy consum<br>mode (kWh/100<br>up to the neares   | 00 h), rounded                   | 8                         | Energy efficiency<br>class  | E            |  |  |
| Useful luminou<br>indicating if it re<br>in a sphere (36<br>cone (120 <sup>o</sup> ) or in<br>(90 <sup>o</sup> ) | efers to the flux 50°, in a wide | 1 055 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 3 000        |  |  |
| On-mode p<br>expressed in W  | ower (P <sub>on</sub> ),         | 8,0                       | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00         |  |  |
| Networked stand<br>for CLS, expres<br>rounded to the s   | sed in W and                     | -                         | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 80           |  |  |
| Outer<br>dimensions<br>without   | Height                           | 108                       | Spectral power  | See image    |  |  |
|  | Width                            | 60                        | distribution in the   | in last page |  |  |
|  | Depth                            | 60                        |   | Pagina 1 / 3 |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) |             | range 250 nm to 800<br>nm, at full-load |       |
|--|-------------|---|-------|
| Claim of equivalent power <sup>(a)</sup>   | -           | If yes, equivalent power (W)            | -     |
|  |             | Chromaticity                            | 0,440 |
|  |             | coordinates (x and y)                   | 0,403 |
| Parameters for LED and OLED ligh   | nt sources: | · · ·                                   |       |
| R9 colour rendering index value  | 9           | Survival factor                         | 0,90  |
| the lumen maintenance factor   | 0,94        |   |       |
| (a)  |             | 1                                       |       |

(a)'-' : not applicable;

(b)'-' : not applicable;

